

14. (new) A combination according to claim 6, wherein said pressure line is a pressurized line of a fire extinguishing system.

15. (new) A combination according to claim 8, wherein said sensor is a pressure, temperature or humidity sensor for monitoring process conditions.


REMARKS

The foregoing amendments are being made to bring the application into conformity to U.S. practice. No new matter has been added.

Examination of the application as amended herein is respectfully requested.

Applicants' undersigned attorney may be reached in our New York office by telephone at (212) 218-2100. All correspondence should continue to be directed to our below listed address.

Respectfully submitted,



William J. Brunet
Attorney for Applicants
Registration No. 20,452


FITZPATRICK, CELLA, HARPER & SCINTO
30 Rockefeller Plaza
New York, New York 10112-3801
Facsimile: (212) 218-2200
NYMAIN#233001v1

4

Application No. 10/050,783
Attorney Docket: 366.158
Applicant: BERND ONDRUSCHKA, ET AL.

VERSION WITH MARKINGS TO SHOW CHANGES TO SPECIFICATION

#233001V1



[Description of the Invention] TITLE

[Device for performing safety functions in areas with high frequency radiation] Device for Performing Safety Functions in Areas with High Frequency Radiation

5

BACKGROUND OF THE INVENTION

Field of the Invention

The invention concerns a device for performing safety functions in areas with high frequency radiation.

- 10 It allows the advantageous detection and removal of hazards when working in areas in which preferably a specified high frequency radiation is used.

Description of the Related Art

- For the running, acceleration and/or initiation of chemical reactions and processes an introduction of energy is often needed. For this purpose the reaction mixtures are arranged
- 15 in a microwave system with a radiation-screened housing in, for example, reaction containers that allow microwaves to pass through them, and energy is introduced through radiation with microwaves. Since with the reactions and processes that take place high pressures often result or the reactions only run under pressure, the entire arrangement must be stable under pressure and, for example, have a locking cover system. As a result in the
- 20 event of an incident as a rule no access can be gained to the source of the danger in order, for example in the event of fire, explosion and so on, to be able to influence the extent of any damage. In general the reaction vessels are also fitted with safety and control devices, in order to be able to monitor the running of the chemical reactions and processes.

- To date, safety devices in areas subject to high frequency energy have been limited merely
- 25 to the acquisition of process parameters such as pressure and temperature, directly in or on the reactor (for example: DE 19 70 04 99 A1, DE 19 74 85 20 A1). These sensors control the supply of energy to the system. Apart from this sensors are used for detecting escapes of organic solvents (US 6,033,912), which in the event of leaks in the reactor system cut off the energy supply in order to reduce the explosion hazard but do not remove the danger.

In conventional reactor systems and chemical plants, state of the art fire-fighting equipment in a variety of designs has been known for a long time. Here systems that are based either on inert gases (CO₂ extinguishing agents, for example [JEP 1 043 045 A2) or also powder- and liquid-based solvents (for example [JUS 5,996,699, WO 00/12177) are used. Here the type of extinguishing agent is determined by the type of combustible or fire-hazard substance.

For large area fire-fighting sprinkler or gassing systems are often used (for example EP 0 046 378, EP 0 801 962, US 5,415,239).

Where fire extinguishing systems are used in the presence of high frequency radiation, apart from the inaccessibility of the point of danger, it is also necessary to take into account the fact that no materials that react with the high frequencies, such as metals and dipolar organic substances, can be introduced into the hazard area. Thus entry by humans is also subject to limits. Because of the well-known effects of high frequency fields and their interaction with living things, polar compounds and metals, the use of conventional safety devices such as fire extinguishers is excluded.

In previous conventional laboratory systems with reactor volumes of below 500 ml and predominantly discontinuous reaction running, the extent of any damage is relatively limited. This aspect is more critical, however, in larger systems and in particular in continuous reaction running. In these reaction areas significantly larger quantities of substances are subject for longer operating times (often unsupervised ongoing trials) to the effect of the high frequency radiation, with hazards such as overheating, explosion of the resultant substances or detonations, increasing accordingly.

SUMMARY OF THE INVENTION

The object of the invention is to create a device that reacts to abnormal operating states with inadmissible overheating and fire hazard in screened and inaccessible areas with high frequency radiation, in order to perform safety functions of the treatment device and to largely prevent or keep within limits damage to this and the substances treated.

The object is achieved according to the invention by a sealed and [pressurised]pressurized tube that projects into the high frequency sample chamber (for example in the area of the so-called rotating field distributor). The tube, or the sealed tube end of this, or a plastic block, comprises a plastic that allows high frequencies to pass through and has a low melting temperature (for example polyethylene). In the event of an abnormal operating temperature in this zone, such as occurs in particular when there is a fire or [carbonisation]carbonization process, the plastic, or at least part of it, melts causing the tube that has become unretentive to release the pressure. With this release the cooling or extinguishing process is directly or indirectly triggered. In a possible embodiment of the device according to the invention, the tube is [pressurised]pressurized directly by the fire extinguishing agent, such as C02, which when the pressure is released then pours over the hazard point. On the other hand, the said drop in pressure in the tube that has become unretentive can also trigger a pressure sensor (valve) for activation of the fire extinguishing or cooling function.

With the device according to the invention, it is possible to use safety devices that have been known for a long time such as fire extinguishing and cooling systems, to perform safety functions in areas under high frequency radiation that are hermetically sealed and inaccessible because of the necessary protection.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is further explained in the following using embodiments shown in the drawing.

These drawings are as follows:

- Figure 1: Basic structure of the device in accordance with the invention, whereby a temperature-sensitive pressure line serves simultaneously as a functional line for introduction of an extinguishing agent of a fire extinguishing system.
- Figure 2: Basic structure of the device in accordance with the invention, whereby a temperature-sensitive, [pressurised]pressurized indicator line is connected via a pressure operated valve with a fire extinguishing system.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

As a safety device an already known fire extinguishing system 1, is provided with a solvent
5 2, such as ~~[pressurised]~~pressurized CO2 (extinguishing gas) and arranged externally to a microwave treatment system. This fire extinguishing system 1 is connected in Figure 1 with an extinguishing line 3 that is ~~[pressurised]~~pressurized with the extinguishing gas 2, and which is run over a flange 4 into a sample chamber 5 of the microwave treatment system, which in a known manner has an air intake 6 and extraction 7. The extinguishing line 3
10 terminates in a pressure-resistant plastic pipe 8, which protrudes into the sample chamber 5. The plastic pipe 8 comprises a material (such as polyethylene, polypropylene, polystyrene or combinations of these and other plastics), that allows microwave radiation to pass through without significant heating and whose melting temperature is only slightly higher than the operationally permitted limiting temperature in the sample chamber 5
15 specific to the treatment. In the event of an abnormally high operating temperature in the sample chamber 5, in particular in the event of a fire 9 or detonation, the temperature-sensitive material of the plastic pipe 8 melts and it loses its pressure-resistance. Because of this the plastic pipe 8 is now destroyed due to the constant pressure exerted internally upon it and releases the extinguishing agent 2 from the fire extinguishing system
20 1 via the now open extinguishing line 3 into the sample chamber 5 (shown symbolically with arrows).

In Figure 2 an indicator line 10 projecting into the sample chamber 5 of the microwave processing system is arranged separately from the extinguisher line 3. The extinguisher line
25 3 is run as in Figure 1 via the flange 4 into the sample chamber 5, but terminates as an open line for introduction of the extinguishing agent 2. Unlike the first embodiment, the extinguisher line 3 of the fire extinguishing system 1 is not ~~[pressurised]~~pressurized by the extinguishing agent 2, but is decoupled from the extinguishing agent 2 via a pressure valve 11 that under normal operating conditions of the microwave treatment system is closed.
30 The pressure valve 11 is locked by a pressure line 12, via which the indicator line, 10 which is likewise connected to the pressure valve 11, is ~~[pressurised]~~pressurized.

The other end of the [pressurised]pressurized indicator line 10 projecting into the sample chamber 5 terminates in a plastic pipe 13 which likewise (like the plastic pipe 8 in Figure 1) comprises a microwave-transparent plastic (such as polyethylene, polypropylene, polystyrene or a combination of these and other plastics) and which in the sample chamber 5 has the same function of temperature indicator as the plastic pipe 8. In the event of abnormal operational heating of the plastic, this melts and releases the pressure within the indicator line 10, the other end of which is connected to the pressure valve 11. This drop in pressure in the indicator line 10 releases the pressure valve 11, which activates the fire extinguishing system 1, so that the extinguishing agent 2 is released and flows via the extinguishing line 3 into the sample chamber 5.

An advantage of this embodiment is that the pressure valve 11 can also be connected to other sensors (for clarity of the drawing not shown in this), such as pressure, temperature and humidity sensors, for monitoring of safety and/or process conditions.

Furthermore, the device -according to the invention is not restricted to the incident mentioned but can, inter alia, be used for controlled cooling of samples in the treatment process. Instead of the fire extinguishing system 1 with the extinguishing agent 2, for example, a cooling system (not explicitly shown in the drawing) with a suitable coolant that works on the treatment process of the microwave treatment system can be present and, as described, can be triggered according to the temperature via the [pressurised]pressurized indicator line 10.

[List of legends

	1	-	Fire extinguishing system
	2	-	Extinguishing agent
	3	-	Extinguishing line
5	4	-	Flange
	5	-	Specimen area
	6	-	Air inlet
	7	-	Extraction
	8, 13	-	Plastic pipe
10	9	-	Fire
	10	-	Indicator line
	11	-	Pressure valve
	12	-	Pressure line]

15

NY_MAIN 232998 v 1

VERSION WITH MARKINGS TO SHOW CHANGES MADE TO CLAIMS

1. (amended) In combination:

a chamber[Device for performing safety functions in areas with high frequency radiation, such as in the sample chamber of a microwave treatment system,] in which a process is carried out such that substances in said chamber are exposed to the effect of one or more high frequency radiation[fields, characterised in that in the chamber (5) with high frequency radiation,]; and

at least one sensor[(8, 13)] that does not react to and does not affect[the] high frequency radiation, said sensor being mounted in said chamber[is arranged] to detect a process-critical state, said sensor being connected with a safety device for controlling the effect of said process-critical state[states such as excess temperatures, which is connected with an already known safety device such as a fire extinguishing system (1) or a cooling unit with inert gases].

2. (amended) A combination[Device] according to claim 1, wherein said[characterised in that the] sensor detects temperature and said safety device includes[(8, 13) for temperature detection is designed as] a pressure line[(3 or 10)] that allows high frequencies to pass through it and[that but]which is located in the chamber, said pressure line having[(5) or protrudes into it with a seal (8, 13) that is pressure-stable and likewise allows high frequencies to pass through it and has] a low melting temperature.

3. (amended) A combination[Device] according to claim 9, wherein said seal[2, characterised in that the pressure stable seal (8, 13) that allows high frequencies to pass through it,] comprises plastic[, for example, polyethylene, polypropylene, polystyrene or a combination of these and other plastics].

4. (amended) A combination[Device] according to claim 2, wherein said[characterised in that the] pressure line is a rigid pipe which extends into said[(3 or 10) is run into the] chamber[(5) as a rigid pipe].

5. (amended) A combination[Device] according to claim 2, wherein said[characterised in that the] pressure line is [(3 or 5) is run into the chamber as] a flexible pipe or tube.

6. (amended) A combination[Device] according to claim 2, wherein said[characterised in that the] pressure line is[at the same time envisaged as] a functional element of said[the] safety device[, such as a pressurised line (3) of a fire extinguishing system (10) for carrying an already known extinguishing agent].

7. (amended) A combination[Device] according to claim 2, further including[characterised in that the pressure line (10) is designed independently of the functional element of the safety device (1), and is connected to] a pressure-sensitive controller connected to said pressure line[, such as a pressure valve (11)] for activation of the safety device[(1)].

8. (amended) A combination[Device] according to claim 7, wherein said[characterised in that the] pressure sensitive controller[(11)] is also connected with at least one other sensor[already known, sensors such as pressure, temperature, and humidity sensors, for monitoring of safety and/or other process conditions].